LOW ENERGY REFRIGERATION



2019 lowenergyrefrigeration.co.nz

CONTENTS



FreshLine FRIDGE	135 Lt	3
Fresh4000 FRIDGES	445 Lt	4—5
FreshLine FREEZER	102 Lt	6
Fresh4000 FREEZERS	312 Lt	7—8
FreshLine FRIDGE / FR	EEZER 120 / 13 Lt	9
FRESH4000 TECHNICA	L SPECIFICATIONS	10—1
ELCOLD XLE RANGE		12
XLE TECHNICAL SPECI	FICATIONS	13
CONTACT DETAILS		14





FreshLine

KS 3135-90

White Cabinet

135 Litres 206 kWhs / Year 840H x 545W x 600D mm







SPECIFICATIONS

UPRIGHT FRIDGE

Fridge Volume (net/gross)
130 / 135 Litres

External Dimensions H / W / D 840 x 545 x 600 mm

Energy Star Rating (NZ / Australia)
2.5

Voltage / Hz (Mains Power Operation)
230 VAC / 50 Hz

Yearly Energy Consumption @ 32°C 206 kWh per year

Daily Energy Consumption @ 32°C 0.56 kWh per day

Yearly Energy Consumption @ 25°C 116 kWh per year

Yearly Energy Consumption @ 18°C 74 kWh per year

Climate Class SN-T 10°C t0 43°C

Control Panel Manual

Defrost Function Cyclic

Interchangeable Door Opening Yes

Door Alarm

Replaceable Door Seal

Internal Lighting LED

Refrigerant / Insulation R600a / Cyclopentane

Noise Level 39 dB(A)

Number of Compressors

FEATURES

Glass Shelves (Total / Adjustable)
4 / 3



The GLASS SHELVES are made with toughened safety glass, and they can be placed in various positions within the cabinet to suit your requirements

Vegetable Drawer 1 Frosted Clear



A large single VEGETABLE STORAGE BIN gives you plenty of room

Door Bottle Holder 1 Frosted Clear



The large DOOR BOTTLE HOLDER is ideal for larger milk bottles

Table Top



If not installing this fridge under your bench top, then the Table Top provides you with extra workspace.

Interchangeable Door



We are able to swap the door to reverse the position of the handle. This is done before despatch to your at no additional cost.



KS 4456-90F
White Cabinet
445 Litres
198 kWhs / Year
1850H x 595W x 650D mm







SPECIFICATIONS

UPRIGHT FRIDGE

Fridge Volume (net/gross) 375 / 445 Litres

External Dimensions H / W / D 1850 x 595 x 650 mm

Energy Star Rating (NZ / Australia)
4

Voltage / Hz (Mains Power Operation) 230 VAC / 50 Hz

Yearly Energy Consumption @ 32°C 198 kWh per year

Daily Energy Consumption @ 32°C 0.54 kWh per day

Yearly Energy Consumption @ 25°C 132 kWh per year

Yearly Energy Consumption @ 18°C 104 kWh per year

Climate Class SN-T 10°C t0 43°C

Control Panel Manual

Defrost Function Full No Frost

Interchangeable Door Opening Yes

Temperature Sensor Electronic

Door Alarm

Replaceable Door Seal Yes

Internal Lighting LED on side

Refrigerant / Insulation R600a / Cyclopentane

Noise Level 41 dB(A)

Number of Compressors

FEATURES

Glass Shelves (Total / Adjustable) 7 / 5



The GLASS SHELVES are made with toughened safety glass, and they can be placed in various positions within the cabinet to suit your requirements

Vegetable Drawer 1 Frosted Clear



A large single VEGETABLE STORAGE BIN gives you plenty of room

Door Bottle Holder 1 Frosted Clear



The large DOOR BOTTLE HOLDER is ideal for larger milk bottles

Full No Frost



Full NoFrost is a ventilated cooling system that gives you a uniform temperature in the cabinet, allowing you to choose where the food is to be placed. In addition, you do not get condensation and ice on the back wall.

FreshZone



FreshZone allows you to store fresh fish, fresh meat, dairy products and vegetables. The low temperature in FreshZone makes the food stay fresh for longer. The FreshZone drawer has SoftClose and is equipped with easy-to-use telescopic extensions that provide extra convenience.



KS 4456-90FX

Brushed Stainless Cabinet

445 Litres 198 kWhs / Year 1850H x 595W x 650D mm





SPECIFICATIONS

UPRIGHT FRIDGE

Fridge Volume (net/gross) 375 / 445 Litres

External Dimensions H / W / D 1850 x 595 x 650 mm

Energy Star Rating (NZ / Australia)
4

Voltage / Hz (Mains Power Operation)
230 VAC / 50 Hz

Yearly Energy Consumption @ 32°C 198 kWh per year

Daily Energy Consumption @ 32°C 0.54 kWh per day

Yearly Energy Consumption @ 25°C 132 kWh per year

Yearly Energy Consumption @ 18°C 104 kWh per year

Climate Class SN-T 10°C t0 43°C

Control Panel Manual

Defrost Function Full No Frost

Interchangeable Door Opening

Temperature Sensor Electronic

Door Alarm

Replaceable Door Seal Yes

Internal Lighting LED on side

Refrigerant / Insulation R600a / Cyclopentane

Noise Level 41 dB(A)

Number of Compressors

FEATURES

Glass Shelves (Total / Adjustable)
7 / 5



The GLASS SHELVES are made with toughened safety glass, and they can be placed in various positions within the cabinet to suit your requirements

Vegetable Drawer 1 Frosted Clear



A large single VEGETABLE STORAGE BIN gives you plenty of room

Door Bottle Holder 1 Frosted Clear



The large DOOR BOTTLE HOLDER is ideal for larger milk bottles

Full No Frost



Full NoFrost is a ventilated cooling system that gives you a uniform temperature in the cabinet, allowing you to choose where the food is to be placed. In addition, you do not get condensation and ice on the back wall.

FreshZone



FreshZone allows you to store fresh fish, fresh meat, dairy products and vegetables. The low temperature in FreshZone makes the food stay fresh for longer. The FreshZone drawer has SoftClose and is equipped with easy-to-use telescopic extensions that provide extra convenience.



FreshLine

FS 3135-90

White Cabinet

102 Litres 193 kWhs / Year 840H x 545W x 600D mm







SPECIFICATIONS

UPRIGHT FREEZER

Freezer Volume (net/gross) 85 / 102 Litres

External Dimensions H / W / D 840 x 545 x 600 mm

Energy Star Rating (NZ / Australia)
3.5

Voltage / Hz (Mains Power Operation)
230 VAC / 50 Hz

Yearly Energy Consumption @ 32°C 193 kWh per year

Daily Energy Consumption @ 32°C 0.53 kWh per day

Yearly Energy Consumption @ 25°C 181 kWh per year

Yearly Energy Consumption @ 18°C 121 kWh per year

Climate Class SN-T 10°C t0 43°C

Control Panel

Defrost Function Manual

Interchangeable Door Opening Yes

High Temperature Alarm Yes

Replaceable Door Seal

Super Freeze Yes

Refrigerant / Insulation R600a / Cyclopentane

Noise Level 42dB(A)

Number of Compressors

1

FEATURES

Manual Control Panel



The easy to use control panel has three coloured indicator lights located on the front indicating mode of the freezer.

Freezer Drawers 3 with Clear Fronts

The large freezer drawers give you a good view of their contents



High Temperature Warning



An audible alarm warns you if the temperature in the cabinet becomes too high. It allows you to react before your food is damaged.

Table Top



If not installing this fridge under your bench top, then the Table Top provides you with extra workspace.

SuperFreeze



SuperFreeze ensures quick freezing of your frozen foods, which will then store for longer. The Super Freeze function is especially important when freezing large amounts of food.



FS 4316-90N
White Cabinet
312 Litres
308 kWhs / Year
1850H x 595W x 650D mm







SPECIFICATIONS

UPRIGHT FREEZER

Freezer Volume (net/gross) 275 / 312 Litres

External Dimensions H / W / D 1850 x 595 x 650 mm

Energy Star Rating (NZ / Australia)
3.5

Voltage / Hz (Mains Power Operation)
230 VAC / 50 Hz

Yearly Energy Consumption @ 32°C 308 kWh per year

Daily Energy Consumption @ 32°C 0.84 kWh per day

Yearly Energy Consumption @ 25°C 255 kWh per year

Yearly Energy Consumption @ 18°C 225 kWh per year

Climate Class SN-T 10°C t0 43°C

Control Panel Manual

Defrost Function Full No Frost

Interchangeable Door Opening

Temperature Sensor Electronic

Door Alarm Yes

Replaceable Door Seal

SuperFreeze Yes

Refrigerant / Insulation R600a / Cyclopentane

Noise Level 42 dB(A)

Number of Compressors

1—Inverter Motor

FEATURES

Big Box / Mega Box



A removable shelf between the 2 upper freezer flaps provides you with an extra high storage space for overly large items, such as tall desserts and the Christmas turkey.

XL Capacity



XL models have an extra large capacity as they have a deeper cabinet.

-15°C Ambient Temperature



The freezer can be placed in ambient temperatures as low as -15 ° C. It allows you to place the freezer in cottage, garage, shed or similar.

Full No Frost



SuperFreeze ensures quick freezing of your frozen foods, which can keep saying longer. The Super Freeze function is especially important when freezing large amounts of food.

Inverter Compressor



The Inverter Compressor gives you a lower sound level. The compressor performance is adapted to the actual needs and thus has minimal energy consumption. There is less wear on the compressor, which therefore lasts longer.



FS 4316-90NX

Brushed Stainless Cabinet

312 Litres 308 kWhs / Year 1850H x 595W x 650D mm







SPECIFICATIONS

UPRIGHT FREEZER

Freezer Volume (net/gross) 275 / 312 Litres

External Dimensions H / W / D 1850 x 595 x 650 mm

Energy Star Rating (NZ / Australia)
3.5

Voltage / Hz (Mains Power Operation)
230 VAC / 50 Hz

Yearly Energy Consumption @ 32°C 308 kWh per year

Daily Energy Consumption @ 32°C 0.84 kWh per day

Yearly Energy Consumption @ 25°C 255 kWh per year

Yearly Energy Consumption @ 18°C 225 kWh per year

Climate Class SN-T 10°C t0 43°C

Control Panel Manual

Defrost Function Full No Frost

Interchangeable Door Opening

Temperature Sensor Electronic

Door Alarm Yes

Replaceable Door Seal

SuperFreeze Yes

Refrigerant / Insulation R600a / Cyclopentane

Noise Level 42 dB(A)

Number of Compressors

1—Inverter Motor

FEATURES

Big Box / Mega Box



A removable shelf between the 2 upper freezer flaps provides you with an extra high storage space for overly large items, such as tall desserts and the Christmas turkey.

XL Capacity



XL models have an extra large capacity as they have a deeper cabinet.

-15°C Ambient Temperature



The freezer can be placed in ambient temperatures as low as -15 ° C. It allows you to place the freezer in cottage, garage, shed or similar.

Full No Frost



SuperFreeze ensures quick freezing of your frozen foods, which can keep saying longer. The Super Freeze function is especially important when freezing large amounts of food.

Inverter Compressor



The Inverter Compressor gives you a lower sound level. The compressor performance is adapted to the actual needs and thus has minimal energy consumption. There is less wear on the compressor, which therefore lasts longer.



FreshLine

KF 3135-90

White Cabinet


120 Litres

230 kWhs / Year

840H x 545W x 600D mm







SPECIFICATIONS

UPRIGHT FRIDGE/FREEZER

Fridge: Freezer Volume (net/gross) 101 / 120: 13 / 13 Litres

External Dimensions H / W / D 840 x 545 x 600 mm

Energy Star Rating (NZ / Australia)

Voltage / Hz (Mains Power Operation) 230 VAC / 50 Hz

Yearly Energy Consumption @ 32°C 230 kWh per year

Daily Energy Consumption @ 32°C 0.63 kWh per day

Yearly Energy Consumption @ 25°C 169 kWh per year

Yearly Energy Consumption @ 18°C 131 kWh per year

Climate Class

SN-T 10°C t0 43°C

Control Panel

Manual

Defrost Function

Cyclic / Manual

Interchangeable Door Opening

High Temperature Alarm No

Replaceable Door Seal

Internal Lighting LED

Refrigerant / Insulation R600a / Cyclopentane

Noise Level 37dB(A)

Number of Compressors

1

FEATURES

Glass Shelves (Total / Adjustable) 3 / 2



The GLASS SHELVES are made with toughened safety glass, and they can be placed in various positions within the cabinet to suit your requirements

Vegetable Drawer



A large single VEGETABLE STORAGE BIN gives you plenty of room

Door Bottle Holder



The large DOOR BOTTLE HOLDER is ideal for larger milk bottles

Table Top



If not installing this fridge under your bench top, then the Table Top provides you with extra workspace.

Door Storage Holders

2



The 2 small door storage shelves are ideal for storing smaller items such as condiments, cheese and eggs





HIGH ENERGY EFFICIENCY

CHEST FREEZER

ENVIRONMENTALLY FRIENDLY

TIMELESS SCANDINAVIAN DESIGN

W Flcold



Reliability and very low Energy Consumption are the most important features of Elcold's XLE range of Danish manufactured Chest Freezers. Perfect for storing large quantities or surplus of food stuffs, not only do you have the security in knowing that the energy it uses is at a minimum, which saves you money on your electricity bill, but due to the thickness of insulation, should there be a power cut, your food will keep at a safe, frozen state for several days*.

Elcold's XLE Chest Freezers have fantastic features, including a lockable handle for secure storage of your freezers contents, an internal light, a front display panel showing the status of your freezer, a removable tray to catch defrost water from the drain & removable internal storage baskets.





All 5 models in Elcold's XLE range of Chest Freezers are very energy efficient.











If the environment is important to you and your family, then it will be comforting to know that Elcold's XLE range of Chest Freezers use R600a, a non-ozone depleting refrigerant.

Denmark has always been a pioneer in the development of freezing units, and for more than 40 years, Elcold has constantly focused on improving products. Elcold has acquired vast experience which today, enables them to make some of the finest and most reliable freezers on the market.




XLE CHEST FREEZER




MODEL	11XLE	21XLE	31XLE	41XLE	51XLE
MODEL	TIXLE	ZIXLE	STALE	41XLE	DIXLE

Exterior Finish Classic White Volume (Net / Gross, Litres) 310 / 130 227 / 227 301 / 301 360 / 360 418 / 418 Height (mm) (A) 720 1050 1300 1500 1700 Depth (excluding handles & hinges) (mm) 650 650 650 650 650 Height (with open lid) (mm) 1560 1560 1560 1560 1560 Internal Dimensions (mm) (Hx G x E/F) 650 x 450 x 520 / 320 650 x 450 x 850 / 650 650 x 450 x 1300 / 1100 650 x 450 x 1300 / 1100 650 x 450 x 1300 / 1100 650 x 450 x 1500 / 1300 1560 <t< th=""><th>Туре</th><th>Chest Freezer</th><th>Chest Freezer</th><th>Chest Freezer</th><th>Chest Freezer</th><th>Chest Freezer</th></t<>	Туре	Chest Freezer	Chest Freezer	Chest Freezer	Chest Freezer	Chest Freezer				
Height (mm) (C) 860	Exterior Finish	Classic White	Classic White	Classic White	Classic White	Classic White				
Width (mm) (A) 720 1050 1300 1500 1700 Depth (including handles & hinges) (mm) 730 730 730 730 730 Depth (excluding handles & hinges) (mm) 650 650 650 650 650 Height (with open lid) (mm) 1560 1560 1560 1560 1560 Internal Dimensions (mm) (H x G x E / F) 650 x 450 x 520 / 320 650 x 450 x 850 / 650 650 x 450 x 1300 / 1100 650 x 450 x 1500 / 1300 ENERGY & TECHNICAL INFORMATION Energy Rating (Star Rating ASINZS) 4 3.5 4 3.5 3.5 Energy Consumption @ 32°C (kWh / YEAR) 177 273 255 319 342 Energy Consumption @ 25°C (kWh / year) 157 201 234 263 296 Energy Consumption @ 18°C (kWh / year) - - - - - Voltage (Mains Power Operation) 230VAC 230VAC 230VAC 230VAC 230VAC Defrost Function, (Manual) • • • • •	Volume (Net / Gross, Litres)	130 / 130	227 / 227	301 / 301	360 / 360	418 / 418				
Depth (including handles & hinges) (mm) 730	Height (mm) (C)	860	860	860	860	860				
Depth (excluding handles & hinges) (mm)	Width (mm) (A)	720	1050	1300	1500	1700				
Height (with open lid) (mm)	Depth (including handles & hinges) (mm)	730	730	730	730	730				
Internal Dimensions (mm) (H x G x E / F) 650 x 450 x 520 / 320 650 x 450 x 850 / 650 650 x 450 x 1100 / 1900 650 x 450 x 1300 / 1100 650 x 450 x 1500 / 1300	Depth (excluding handles & hinges) (mm)	650	650	650	650	650				
ENERGY & TECHNICAL INFORMATION Energy Rating (Star Rating AS/NZS)	Height (with open lid) (mm)	1560	1560	1560	1560	1560				
Energy Rating (Star Rating AS/NZS)	Internal Dimensions (mm) (H x G x E / F)	650 x 450 x 520 / 320	650 x 450 x 850 / 650	650 x 450 x 1100 / 1900	650 x 450 x 1300 / 1100	650 x 450 x 1500 / 1300				
Energy Consumption @ 32°C (kWh / YEAR) 177 273 255 319 342 Energy Consumption @ 32°C (kWh / DAY) 0.48 0.75 0.70 0.87 0.94 Energy Consumption @ 25°C (kWh / DAY) 157 201 234 263 296 Energy Consumption @ 18°C (kWh / year)	ENERGY & TECHNICAL INFORMATION									
Energy Consumption @ 32°C (kWh / DAY)	Energy Rating (Star Rating AS/NZS)	4	3.5	4	3.5	3.5				
Energy Consumption @ 25°C (kWh / year) 157 201 234 263 296 Energy Consumption @ 18°C (kWh / year)	Energy Consumption @ 32°C (kWh / YEAR)	177	273	255	319	342				
Energy Consumption @ 18°C (kWh / year)	Energy Consumption @ 32°C (kWh / DAY)	0.48	0.75	0.70	0.87	0.94				
Voltage (Mains Power Operation) 230VAC	Energy Consumption @ 25°C (kWh / year)	157	201	234	263	296				
Defrost Function, (Manual) • • • • Freezing Capacity (kg / 24hrs) 16 25 31 34 36 Temperature Rise to −9°C (hrs) 52 60 64 66 66 Refrigerant R600a R600a R600a R600a R600a R600a SPECIAL FEATURES OF THE XLE CHEST FREEZER Insulation Thickness (mm) 100 100 100 100 100 Handle with lock • • • • • • Calendar in Lid • • • • • • Light in Lid • • • • • • Number of Baskets 1 2 3 4 4 Removable Divider • • • • • Lamps in Front Display Panel 3 3 3 3 3	Energy Consumption @ 18°C (kWh / year)	-	-	-	-	-				
Freezing Capacity (kg / 24hrs) 16 25 31 34 36 Temperature Rise to -9°C (hrs) 52 60 64 66 66 Refrigerant R600a R600a R600a R600a R600a R600a SPECIAL FEATURES OF THE XLE CHEST FREEZER Insulation Thickness (mm) 100 100 100 100 100 Handle with lock • • • • • • Calendar in Lid • • • • • • Light in Lid • • • • • • Number of Baskets 1 2 3 4 4 Removable Divider • • • • • Lamps in Front Display Panel 3 3 3 3 3	Voltage (Mains Power Operation)	230VAC	230VAC	230VAC	230VAC	230VAC				
Temperature Rise to -9°C (hrs) 52 60 64 66 66 Refrigerant R600a R600a R600a R600a R600a R600a SPECIAL FEATURES OF THE XLE CHEST FREEZER Insulation Thickness (mm) 100 100 100 100 100 Handle with lock • • • • • • Calendar in Lid • • • • • • Light in Lid • • • • • • Number of Baskets 1 2 3 4 4 Removable Divider • • • • • Lamps in Front Display Panel 3 3 3 3 3 3	Defrost Function, (Manual)	•	•	•	•	•				
Refrigerant R600a	Freezing Capacity (kg / 24hrs)	16	25	31	34	36				
SPECIAL FEATURES OF THE XLE CHEST FREEZER Insulation Thickness (mm) 100	Temperature Rise to -9°C (hrs)	52	60	64	66	66				
Insulation Thickness (mm) 100 100 100 100 100 Handle with lock • • • • • • Calendar in Lid • • • • • • Light in Lid • • • • • • Number of Baskets 1 2 3 4 4 Removable Divider • • • • • Lamps in Front Display Panel 3 3 3 3 3	Refrigerant	R600a	R600a	R600a	R600a	R600a				
Handle with lock	SPECIAL FEATURES OF THE XLE CHEST FREEZER									
Calendar in Lid • • • • Light in Lid • • • • • Number of Baskets 1 2 3 4 4 Removable Divider • • • • • • Lamps in Front Display Panel 3 3 3 3 3 3	Insulation Thickness (mm)	100	100	100	100	100				
Light in Lid • • • • • Number of Baskets 1 2 3 4 4 Removable Divider • • • • • Lamps in Front Display Panel 3 3 3 3 3	Handle with lock	•	•	•	•	•				
Number of Baskets 1 2 3 4 4 Removable Divider • • • • • Lamps in Front Display Panel 3 3 3 3 3	Calendar in Lid	•	•	•	•	•				
Removable Divider • • • Lamps in Front Display Panel 3 3 3 3	Light in Lid	•	•	•	•	•				
Lamps in Front Display Panel 3 3 3 3 3	Number of Baskets	1	2	3	4	4				
	Removable Divider	•	•	•	•	•				
Defrost Drain • • • • •	Lamps in Front Display Panel	3	3	3	3	3				
	Defrost Drain	•	•	•	•	•				

Subject to alterations. The technical specifications should be taken as a guidance. All Elcold models come with a standard 2 year limited warranty.





FOR ENQUIRIES PLEASE CONTACT

NEW ZEALAND



POSTAL ADDRESS: PO Box 35243, Browns Bay, AUCKLAND 0753, NEW ZEALAND

PHYSICAL ADDRESS: 32e William Pickering Drive, Rosedale, AUCKLAND 0632, NEW ZEALAND

PHONE: +64 9 415 6686 FAX: +64 9 415 6685

WEBSITE: www.lowenergyrefrigeration.co.nz / www.chestfreezer.co.nz

WEBSITE: www.indepower.co.nz EMAIL: ler@indepower.co.nz

PACIFIC ISLANDS





POSTAL ADDRESS: PO Box 2395, Government Buildings, SUVA, FIJI ISLANDS

PHYSICAL ADDRESS: 13 Carpenter Street, Raiwai, SUVA, FIJI ISLANDS

PHONE: +679 336 3880

WEBSITE: www.gram.co.nz / www.elcold.co.nz / www.lowenergyrefrigeration.co.nz

WEBSITE: www.clayenergy.com.fj EMAIL: sales@clayenergy.com.fj



